

Specifications Sheet for Corrugated PetroDuct™



PETROFLEX NORTH AMERICA, Ltd.
ADVANCED PEDESTALS, Ltd.

Specifications Sheet for Corrugated PetroDuct™

All PetroDuct™ is available pre-lubed, with pulling rope pre-installed; and in other sizes and lengths as a special order. Joints are available in all sizes.

Standard Specifications for Corrugated PetroDuct™

| Product Part # | SDR/SC H Rating | Nominal O.D. | Min I.D. | Min Wall | Max Wall | Weight lbs/ft. | Mean Density | Mean Wall |
|---|-----------------|--------------|----------|----------|----------|----------------|--------------|-----------|
| PC100 | N/A | 1.300 | 1.000 | 0.50 | 0.080 | 0.1051 | 0.950 | 0.066 |
| PC100-FR | N/A | 1.300 | 1.000 | 0.50 | 0.080 | 0.1051 | 0.950 | 0.066 |
| PC100-PL | N/A | 1.300 | 1.000 | 0.014 | 0.034 | 0.1001 | 0.950 | 0.024 |
| PC125 | N/A | 1.540 | 1.250 | 0.50 | 0.080 | 0.1502 | 0.950 | 0.060 |
| PC125-FR | N/A | 1.540 | 1.250 | 0.50 | 0.080 | 0.1502 | 0.950 | 0.060 |
| PC125-PL | N/A | 1.540 | 1.250 | 0.017 | 0.031 | 0.1450 | 0.950 | 0.024 |
| PC200 | N/A | 2.315 | 2.000 | 0.030 | 0.050 | 0.1902 | 0.950 | 0.040 |
| PC=Corrugated PL=Plenum Rated FR=Flame Retardant | | | | | | | | |