

Specifications Sheet for Plenum-Rated PetroDuct™



PETROFLEX NORTH AMERICA, Ltd.
ADVANCED PEDESTALS, Ltd.

Specifications Sheet for Plenum-Rated PetroDuct™

All PetroDuct™ is available pre-lubed, with pulling rope pre-installed; and in other sizes and lengths as a special order. Joints are available in all sizes.

Standard Specifications for Plenum-Rated PetroDuct™

Product Part #	SDR/SC H Rating	Nominal O.D.	Min I.D.	Min Wall	Max Wall	Weight lbs/ft.	Mean Density	Mean Wall
PC100	N/A	1.300	1.000	0.50	0.080	0.1051	0.950	0.066
PC100-FR	N/A	1.300	1.000	0.50	0.080	0.1051	0.950	0.066
PC100-PL	N/A	1.300	1.000	0.014	0.034	0.1001	0.950	0.024
PC125	N/A	1.540	1.250	0.50	0.080	0.1502	0.950	0.060
PC125-FR	N/A	1.540	1.250	0.50	0.080	0.1502	0.950	0.060
PC125-PL	N/A	1.540	1.250	0.017	0.031	0.1450	0.950	0.024
PC200	N/A	2.315	2.000	0.030	0.050	0.1902	0.950	0.040
PC=Corrugated PL=Plenum Rated FR=Flame Retardant								