

Specifications Sheet for Ribbed PetroDuct™



PETROFLEX NORTH AMERICA, Ltd.
ADVANCED PEDESTALS, Ltd.

Specifications Sheet for Ribbed PetroDuct™

All PetroDuct™ is available pre-lubed, with pulling rope pre-installed; and in other sizes and lengths as a special order. Joints are available in all sizes.

Standard Specifications for Ribbed PetroDuct™

| Product Part # | SDR/SCH Rating | Nominal O.D. | Min I.D. | Min Wall | Max Wall | Weight lbs/ft. | Mean Density | Mean Wall |
|----------------|----------------|--------------|----------|----------|----------|----------------|--------------|-----------|
| PR100-2 | SDR17 | 1.315 | 1.091 | 0.077 | 0.097 | 0.1437 | 0.950 | 0.087 |
| PR100-2 | SDR13.5 | 1.315 | 1.051 | 0.097 | 0.117 | 0.1727 | 0.950 | 0.107 |
| PR100-2 | SDR11 | 1.315 | 1.005 | 0.120 | 0.140 | 0.2048 | 0.950 | 0.130 |
| PR100-2 | SDR9 | 1.315 | 0.953 | 0.146 | 0.166 | 0.2394 | 0.950 | 0.156 |
| PR118-2 | SDR15.5 | 1.420 | 1.166 | 0.092 | 0.112 | 0.1799 | 0.950 | 0.102 |
| PR118-2 | SDR13.5 | 1.420 | 1.140 | 0.105 | 0.125 | 0.2002 | 0.950 | 0.115 |
| PR125-2 | SDR17 | 1.660 | 1.394 | 0.098 | 0.118 | 0.2369 | 0.950 | 0.108 |
| PR125-2 | SDR13.5 | 1.660 | 1.310 | 0.125 | 0.145 | 0.2708 | 0.950 | 0.135 |
| PR125-2 | SDR11.5 | 1.660 | 1.272 | 0.144 | 0.164 | 0.3061 | 0.950 | 0.154 |
| PR125-2 | SDR11 | 1.660 | 1.258 | 0.151 | 0.171 | 0.3203 | 0.950 | 0.161 |
| PR125-2 | SCH40 | 1.660 | 1.310 | 0.140 | 0.160 | 0.3098 | 0.950 | 0.150 |
| PR150-2 | SDR17 | 1.900 | 1.586 | 0.112 | 0.132 | 0.3107 | 0.950 | 0.122 |
| PR150-2 | SDR13.5 | 1.900 | 1.518 | 0.141 | 0.161 | 0.4217 | 0.950 | 0.151 |
| PR150-2 | SDR11 | 1.900 | 1.444 | 0.173 | 0.194 | 0.4145 | 0.950 | 0.183 |
| PR150-2 | SCH40 | 1.900 | 1.520 | 0.145 | 0.165 | 0.3800 | 0.950 | 0.155 |
| PR200-2 | SDR17 | 2.375 | 1.995 | 0.140 | 0.160 | 0.4418 | 0.950 | 0.150 |
| PR200-2 | SDR13.5 | 2.375 | 1.921 | 0.176 | 0.197 | 0.5368 | 0.950 | 0.186 |
| PR200-2 | SDR11 | 2.375 | 1.831 | 0.216 | 0.242 | 0.6458 | 0.950 | 0.229 |
| PR200-2 | SCH40 | 2.375 | 1.967 | 0.154 | 0.174 | 0.4792 | 0.950 | 0.164 |
| PR100-2 | SIDR13 | 1.270 | 1.008 | 0.091 | 0.111 | 0.1582 | 0.950 | 0.101 |
| PR125-2 | SIDR11.5 | 1.660 | 1.320 | 0.120 | 0.140 | 0.2673 | 0.950 | 0.130 |
| PR125-2 | SIDR9 | 1.700 | 1.294 | 0.153 | 0.173 | 0.3292 | 0.950 | 0.163 |

Ribbed products contain a -2 at the end of the part number.

PR###-2: The ### indicates size. For instance PR100-2 is a 1" Ribbed PetroDuct™ and PR125-2 is a 1 1/4" Ribbed PetroDuct™.