


UL LISTED Conduit

Petroduct/HDPE/Smooth/Smooth



Petroflex Petroduct* UL Listed smoothwall HDPE conduit is ideal for installation of cable in any application. Petroduct smoothwall can also be manufactured with cable installed at the factory.

Features:

- * Made from Prime HDPE Pipe Grade Resin
- * Smooth inner wall
- * Available with pre-installed tape or empty, with PNA or customer-supplied cable
- * Available pre-lubricated with Petroflex's own ProPull* Lube
- * Sequential footage and UL Listed markings every two feet
Custom print lines available
- * Packaged on lightweight steel reels or in coils
(Minimum orders apply per size)
- * Manufactured to ASTM D2447, D3035(F2160), D1248, D1693, D3350 and NEMA TC7 Specifications
- * Listed to UL 651, UL 1990
Compliant with the 2005 NEC Article 353
- * 2, 3, or 4 colors available paralleled onto one reel as a special order(see reel chart)
- * Conforms to NEMA TC-7 Smoothwall
Coilable PE Electrical Plastic Conduit

<u>Size</u>	<u>Part #</u>	<u>Min. I.D.</u>	<u>Nom. O.D.</u>	<u>Mean Wall</u>	<u>Weight lbs./ft</u>
1.00"	P100EPEC-B	1.080	1.315	0.107	0.1672
	P100SCH40-UL	1.009	1.315	0.143	0.2168
	P100SCH80-UL	0.917	1.315	0.189	0.2754
1.25"	P125EPEC-B	1.374	1.660	0.133	0.2628
	P125SCH40-UL	1.340	1.660	0.150	0.2931
	P125SCH80-UL	1.232	1.660	0.201	0.3827
1.50"	P150EPEC-A	1.630	1.900	0.125	0.2871
	P150EPEC-B	1.579	1.900	0.141	0.3417
	P150SCH40-UL	1.570	1.900	0.145	0.3500
	P150SCH80-UL	1.452	1.900	0.200	0.4630
2.00"	P200EPEC-B	1.981	2.375	0.186	0.5268
	P200SCH40-UL	2.027	2.375	0.164	0.4692
	P200SCH80-UL	1.887	2.375	0.231	0.6408
2.50"	P250EPEC-B	2.397	2.875	0.226	0.7746
	P250SCH40-UL	2.421	2.875	0.215	0.2150
	P250SCH80-UL	2.257	2.875	0.293	0.2930
3.00"	P300EPEC-B	2.919	3.500	0.274	1.1437
	P300SCH80-UL	2.828	3.500	0.318	1.3092
4.00"	P400EPEC-B	3.753	4.500	0.353	1.8941
	P400SCH80-UL	3.746	4.500	0.357	1.9137