



MATERIAL SAFETY DATA SHEET

SECTION 1 - IDENTIFICATION

CHEMICAL NAME & SYNONYMS:

ProPull Duct / Cable Lube™

CHEMICAL FAMILY:

Chemical Mixture.

FORMULA:

PRODUCT:

Cable-Lube.

DESCRIPTION:

Transparent liquid (water polymer gel) & cosmetic grade chemicals.

APPLICATION:

FOR FIELD USE.

SECTION II - NORMAL HANDLING PROCEDURES

PRECAUTIONS TO BE TAKEN IN HANDLING & STORAGE:

Do not get in eyes, on skin or clothing. Do not take internally. Avoid breathing mist or vapor. Upon contact with eyes, wash off with water.

PROTECTIVE EQUIPMENT:

Safety glasses with side shields; gloves/other not required.

VENTILATION REQUIREMENTS:

None normally required beyond good room ventilation.

SECTION III - HAZARDOUS INGREDIENTS

BASIC MATERIAL:

No hazardous ingredients per OSHA definitions.

OSHA PEL:

None established.

LD 50:

LC 50:

SIGNIFICANT EFFECTS:

SECTION IV - FIRE & EXPLOSION HAZARD DATA

FLASH POINT METHOD:

N/A

OSHA CLASSIFICATION:

Liquid non-combustible

FLAMMABLE EXPLOSIVE LIMIT:

UPPER:

N/A

LOWER:

N/A

EXTINGUISHING MEDIA:

Waterspray, dry chemical, alcohol foam or carbon dioxide.

SPECIAL FIRE HAZARD & FIRE FIGHTING PROCEDURES:

Use NIOSH/MSHA-approved self-contained breathing apparatus where this material is involved in a fire.

SECTION V - HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE:

None established.

SYMPTOMS OF OVEREXPOSURE:

Diarrhea, lethargy by oral ingestion, otherwise practically non-toxic.

EMERGENCY FIRST AID PROCEDURES:

SKIN: Flush with water. Washing any substance off skin is a good safety practice.

EYES: Flush with water. If eye irritation develops, call physician.

INGESTION: Drink water to dilute. **INHALATION:** Remove victim to fresh air.

SECTION VI - TOXICOLOGY (PRODUCT)

ACUTE ORAL LD 50:

ACUTE DERMAL LD:

ACUTE INHALATION:

None established.

None established.

None established.

CARCINOGENICITY:

MUTAGENICITY:

Not known to be carcinogenic.

Not known to be mutagenic.

EYE IRRITATION:

PRIMARY SKIN IRRITATION:

Not an irritant.

Not an irritant.

SECTION VII - SPILL & LEAKAGE (CONTROL) PROCEDURE

ACTION FOR MATERIAL RELEASE OR SPILL:

Wear goggles, coveralls, impervious gloves and boots. Add dry absorbent, shovel or sweep up. Place in an appropriate container and seal. Wash all contaminated clothing before reuse. In the event of a large spill, call:

**TRANSPORTATION EMERGENCY, CONTACT:
PETROFLEX N.A. - (800) 433-5711**

WASTE DISPOSAL METHOD:

Dispose of contaminated product, empty containers and materials used in cleaning up spills or leaks in manner approved for this material. Consult appropriate Federal, State and local regulatory agencies to ascertain proper disposal procedures.

SECTION VIII - SHIPPING DATA

APPLICABLE REGULATIONS:

Department of Transportation - NOT REGULATED.

SECTION IX - REACTIVITY DATA

STABILITY:

HAZARDOUS POLYMERIZATION

Stable - At _____°C _____°F

May occur. Will not occur.

CONDITIONS TO AVOID:

INCOMPATIBILITY (MATERIALS TO AVOID):

High heat.

Strong oxidizers.

HAZARDOUS DECOMPOSITION PRODUCTS:

Carbon monoxide, carbon dioxide.

SECTION X - PHYSICAL DATA

Melting Point: 10° to 30° F

Vapor Pressure: No data.

Volatiles: No data.

Boiling Point: 214° F

Solubility In Water: Miscible.

Evaporation Rate: No data.

Specific Gravity: 1.05

Ph: 7

Vapor Density (Air=1): No data.

ProPull Lube is a Trademark of Petroflex N.A., Inc.
The information herein is provided in good faith based on experimental data. The manufacturer's only liability shall be to replace that quantity of product proven to be defective. Petroflex N.A., Inc., assumes no liability for any loss, injury or damage to person or property associated with the use or misuse of ProPull Lube. The user assumes all risk and liability with respect to intended applications. All specifications are subject to change.