


## UL LISTED Conduit

### Petroduct/HDPE/Smooth/Smooth



Petroflex Petroduct™ UL Listed smooth wall HDPE conduit is ideal for installation of cable in any application. Petroduct smooth wall can also be manufactured with cable installed at the factory.

#### Features:

- \* Made from Prime HDPE Pipe Grade Resin
- \* Smooth inner wall
- \* Available with pre-installed tape or empty, with PNA or customer-supplied cable
- \* Available pre-lubricated with Petroflex's own ProPull\* Lube
- \* Sequential footage and UL Listed markings every two feet  
Custom print lines available
- \* Packaged on lightweight steel reels or in coils  
(Minimum orders apply per size)
- \* Manufactured to ASTM D2447, D3035(F2160), D1693, D3350, D3485 and NEMA TC7 Specifications
- \* Listed to UL 651A, UL 1990  
Compliant with the latest NEC Article 353
- \* 2, 3, or 4 colors available paralleled onto one reel as a special order(see reel chart)
- \* Conforms to NEMA TC-7 Smoothwall  
Coilable PE Electrical Plastic Conduit

\*R prefix to any part # indicates cut-to-length & does not change fit, form or function (i.e. RP150SCH40UL, RP125SCH80UL)

\*CS or PS prefix to any part # indicates pre-installed cable in conduit & does not change fit, form or function (i.e. CSP200SCH40UL, PSP150SCH80UL)

<u>Size</u>	<u>Part #</u>	<u>Min. I.D.</u>	<u>Nom. O.D.</u>	<u>Mean Wall</u>	<u>Weight lbs./ft</u>
1.00"	P100EPEC-B	1.080	1.315	0.107	0.1672
	P100SCH40UL	1.009	1.315	0.143	0.2168
	P100SCH80UL	0.917	1.315	0.189	0.2754
1.25"	P125EPEC-B	1.374	1.660	0.133	0.2628
	P125SCH40UL	1.340	1.660	0.150	0.2931
	P125SCH80UL	1.232	1.660	0.201	0.3827
1.50"	P150EPEC-A	1.630	1.900	0.125	0.2871
	P150EPEC-B	1.579	1.900	0.141	0.3417
	P150SCH40UL	1.570	1.900	0.145	0.3500
	P150SCH80UL	1.452	1.900	0.200	0.4630
2.00"	P200EPEC-B	1.981	2.375	0.186	0.5268
	P200SCH40UL	2.027	2.375	0.164	0.4692
	P200SCH80UL	1.887	2.375	0.231	0.6408
2.50"	P250EPEC-B	2.397	2.875	0.226	0.7746
	P250SCH40UL	2.421	2.875	0.215	0.7400
	P250SCH80UL	2.257	2.875	0.293	0.9774
3.00"	P300EPEC-B	2.919	3.500	0.274	1.1437
	P300SCH40UL	3.016	3.500	0.229	0.9692
	P300SCH80UL	2.828	3.500	0.318	1.3092
4.00"	P400EPEC-B	3.753	4.500	0.353	1.8941
	P400SCH40UL	3.970	4.500	0.252	1.3851
	P400SCH80UL	3.746	4.500	0.357	1.9137