

PETROTRIB™

For Specialized installation of underground cable, including fiber and optics, PetroRib™ conduit provides superior friction reduction and flexibility. Manufactured from quality High Density Polyethylene resin, PetroRib™ offers maximum strength and adaptability on long pulls with numerous turns and elevation changes. PetroRib™ also affords superior pulling ease and lubrication effectiveness when installed with ProPull™ Lube.

Features:

- Made with Prime HDPE Pipe Grade Resin
- Ribbed inner wall
- Available with pre-installed tape or as empty duct
- Available pre-lubricated with Petroflex's own ProPull™ Lube
- Sequential footage markings every two feet
- Packaged on lightweight steel reels or in coils
- Manufactured to ASTM D2447, D3035, D3485, D2239, F2160 and NEMA TC7 Specifications
- Standard Colors (Striping is available)

*R prefix to any part # indicates cut-to-length & does not change fit, form or function (i.e. RPR100SDR13.5, RPR150SDR13.5)



PETRORIB™



Standard Specifications for PETRORIB™

| Size | Product Part# | Nominal O.D. | Min. I.D. | Weight LBS/Ft. | Mean Wall |
|-------|---------------|--------------|-----------|----------------|-----------|
| 1.00" | PR100SDR13.5 | 1.315 | 1.101 | 0.1727 | 0.107 |
| | PR100SDR11 | 1.315 | 1.055 | 0.2048 | 0.130 |
| | PR100SCH40 | 1.315 | 0.979 | 0.2223 | 0.143 |
| 1.25" | PR125SDR13.5 | 1.660 | 1.340 | 0.2708 | 0.135 |
| | PR125SDR11 | 1.660 | 1.258 | 0.3203 | 0.161 |
| | PR125SCH40 | 1.660 | 1.310 | 0.3098 | 0.150 |
| 1.50" | PR150SDR13.5 | 1.900 | 1.518 | 0.4217 | 0.151 |
| | PR150SDR11 | 1.900 | 1.444 | 0.4145 | 0.183 |
| | PR150SCH40 | 1.900 | 1.520 | 0.3800 | 0.155 |
| 2.00" | PR200SDR13.5 | 2.375 | 1.921 | 0.5368 | 0.186 |
| | PR200SDR11 | 2.375 | 1.831 | 0.6458 | 0.229 |
| | PR200SCH40 | 2.375 | 1.967 | 0.4792 | 0.164 |

