



Applied during extrusion, the exclusive Petroflex process prelubes duct with a high polarity polymeric lubricant. ProPull™ Prelube is completely effective from 20° to 250°. Prelube will not harm HDPE or insulation on cable, and does not contain silicone.

ProPull™ cable lubricant provides non-separating disbursement in all sizes and shapes of duct. Its unique ionic polarity helps prevent friction and burn-through. These physical properties allow vertical pulls without losing effectiveness even in extreme temperatures. It will not evaporate, crystallize or deteriorate, and can be used in other duct materials such as fiberglass and PVC. Virtually non-toxic and bio-degradable, ProPull™ Cable Lubricant does not contain silicone.



Available sizes include Quarts, Gallons, and 5 Gallon Pails

Quantities of ProPull™ Lubricant in Lubricant in Gallons

Duct Size	500	1000	2000	3000	4000	5000
(IPS)	Feet	Feet	Feet	Feet	Feet	Feet
1"	0.5	1	2	3	4	5
1-1/4"	0.6	1.25	2.5	3.75	5	6.25
1-1/2"	0.75	1.5	3	4.5	6	7.5
2"	1	2	4	6	8	10
2-1/2"	1.25	2.5	5	7.5	10	12.5
3"	1.5	3	6	9	12	15
4"	2	4	8	12	16	20
5"	2.5	5	10	15	20	25
6"	3	6	12	18	24	30

MSDS available upon request.